

	SV08-1C	SV10	ViO12-2A	SV17vT	SV17E ⚡	ViO17	SV20vT	ViO23-6	SV26-7	ViO27-7	ViO33-7
EINSATZGEWICHT • POIDS EN ORDRE DE MARCHÉ • PESO OPERATIVO	1 035 kg	1 180 kg	1 245 kg	1 700/1790*** kg	1 865/1 955*** kg	1 830 kg	1 880/1 970*** kg	2 245/2 405*** kg	2 680/2 775*** kg	2 650 kg/2 745 kg	3 265/3 390 kg
GESAMTBREITE • LARGEUR TOTALE • INGOMBRO TRASVERSALE	680 - 840** mm	740 - 990** mm	830 - 1 000** mm	980 - 1 320** mm	980/1 320** mm	955 - 1 280** mm	980 - 1 320** mm	1 380 – 1 550** mm	1 500 - 1 550** mm	1 500 - 1 550** mm	1 550 mm
GRABTIEFE • PROFONDEUR DE CREUSEMENT • PROFONDITÀ DELLA TOMBA	1 460 mm	1 800 mm	1 950 mm	2 470/2 620* mm	2 600/2 750*** mm 2 610 / 2 755*** mm	2 160/2 310* mm	2 470/2 760* mm	2 270/2 465* mm	2 590/2 835* mm	2 590 /2 835 mm	2 830/3 075* mm
GRABKRAFT (ARM) • FORCE DE CAVAGE (BRAS) • FORZA DI SCAVO (AVAMBRACCIO)	5,9 kN	7,6 kN	5,8 kN	9,9/8,9* kN	9,9/8,9* kN	9,6/8,6* kN	11,4/9,3* kN	13,1/10,6* kN	16,5/13,6* kN	16.5/13.6* kN	18,6/16,8* kN
GRABKRAFT (SCHAUFEL) • FORCE DE CAVAGE (GODET) • FORZA DI SCAVO (BENNA)	10 kN	13,7 kN	13,9 kN	16 kN	16 kN	16,1 kN	16,7 kN	17,5 kN	21,4 kN	21,4 kN	30,7 kN
NETTOLEISTUNG • PUISSANCE NETTE • POTENZA NETTA	7,5 kW/2 400 U/min 10,2 PS	9,2 kW/2 000 U/min 12,5 PS	9,2 kW/2 000 U/min 12,5 PS	11,3 kW/2 400 U/min 15,4 PS	 18,3 kWh 24,9 PS	10,1 kW 13,7 PS	13,1 kW/2 100 U/min 18,3 PS	14,6 kW/2 400 U/min 19,9 PS	17,7 kW/2 430 U/min 24,1 PS	17,7 kW/2 400 U/min 24,1 PS	18,5 kW/2 200 U/min 25,0 PS



	ViO38-7	SV39-7	ViO50-6B	ViO57-6B	SV60-6B	ViO80-1	SV86-7	SV86-7 (2PB)	SV100-7	SV100-7 (2PB)
EINSATZGEWICHT • POIDS EN ORDRE DE MARCHÉ • PESO OPERATIVO	3 585/3 710 kg	3 670/3 790*** kg	4 875 kg	5 505 kg	5 655 kg	8 065 kg	8 675 kg	8 985 kg	9 705 kg	10 360 kg
GESAMTBREITE • LARGEUR TOTALE • INGOMBRO TRASVERSALE	1 740 mm	1 740 mm	1940 mm	1 990 mm	1 990 mm	2 270 mm	2 290 mm	2 290 mm	2 320 mm	2 320 mm
GRABTIEFE • PROFONDEUR DE CREUSEMENT • PROFONDITÀ DELLA TOMBA	3 125/3 375* mm	3 125/3 375* mm	3 360/3 610* mm	3 650/3 945* mm	3 650/3 945* mm	4 130/4 500* mm	4 100/4 450* mm	4 120 mm	4 290/4 680* mm	4 330 mm
GRABKRAFT (ARM) • FORCE DE CAVAGE (BRAS) • FORZA DI SCAVO (AVAMBRACCIO)	20,8/18,9 kN	20,8/18,9* kN	22,7/21* kN	24,4/22,2* kN	27,3/24,8* kN	40,8/35,9* kN	39,6/35,9 kN	39,6/-kN	45,9/42,2 kN	45,8 kN
GRABKRAFT (SCHAUFEL) • FORCE DE CAVAGE (GODET) • FORZA DI SCAVO (BENNA)	32,8 kN	32,8 kN	36,5 kN	41,9 kN	41,9 kN	63,5 kN	61,3 kN	61,3 kN	68,4 kN	68,5 kN
NETTOLEISTUNG • PUISSANCE NETTE • POTENZA NETTA	18,5 kW/2200 U/min 25,0 PS	18,5 kW/2200 U/min 25,0 PS	27,5 kW/2 200 (DPF) U/min 37,4 PS	33,5 kW/2 200 (DPF) U/min 45,6 PS	33,5 kW/2 200 (DPF) U/min 45,6 PS	39,3 kW/1 900 (DPF) U/min 53,4 PS	48,0 kW/1 800 (DPF) U/min 65,3 PS	48 kW/1 800 U/min 65,3 PS	51,0 kW/2 100 (DPF) U/min 69,4 PS	51,7 kW/2 100 U/min 69,4 PS



Radlader • Chargeuses sur pneus • Pale gommate

	V7/V7-HW	V8E ⚡	V80	V70s	V100	V120
EINSATZGEWICHT • POIDS EN ORDRE DE MARCHE • PESO OPERATIVO	4 250/4 450 kg	4 500 kg	4 900 kg	5 400 kg	5 800 kg	7 000 kg
LÖFFELINHALT • CAPACITÉ DU GODET • CAPACITÀ BENNA	0,7 - 1,2 m³	0,8 - 1,2 m³	0,8 - 1,2 m³	0,7 - 1,0 m³	1,0 - 1,5 m³	1,2 - 1,8 m³
KIPPLAST (GERADE) • CHARGE DE BASCULEMENT (DROITE) • CARICO RIBALTABILE (DRITTO)	3 000/3 250 kg	3 350 kg	3 770 kg	3 950 kg	4 370 kg	5 000 kg
KIPPLAST (SCHAUFEL) • CHARGE DE BASCULEMENT (GODET) • CARICO DI RIBALTAMENTO (BENNA)	2 650/2 870 kg	2 950 kg	3 330 kg	3 490 kg	3 860 kg	4 400 kg
PUMPENFÖRDERMENGE • DÉBIT DE LA POMPE • PORTATA DELLA POMPA	63/250 l/min	63/250 l/min	65/250 l/min	65/250 l/min	76/250 l/min	81/250 l/min
LEISTUNG • PUISSANCE • POTENZA	35,5 kW / 2 400 U/min 48,3 PS	 39,8 kW 54,1 PS	46,2 kW / 2 200 U/min 62,8 PS	46,2 kW / 2 200 U/min 62,8 PS	53,7 kW / 2 200 U/min 73,0 PS	74,4 kW / 2 000 U/min 101,2 PS



KOMPAKTMASCHINEN
DAS GANZE SORTIMENT

MACHINES COMPACTES • MACCHINE COMPATTE
TOUTE LA GAMME • L'INTERA GAMMA









Exklusiv bei RUBAG

In esclusiva da RUBAG



Raupentransporter • Carriers • Trasportatori

	POWER		POWER+		C08-A HI TIP		HI TIP+		turning vessel		C08E ⚡ POWER, POWER+, HI TIP, HI TIP+, turning vessel	C12R-C	C30R-3	C30R-3TV	C50R-5B	C50R-5BTV
	C08-A (Diesel)	C08-AG (Petrol)	C08-A (Diesel)	C08-AG (Petrol)	C08-A (Diesel)	C08-AG (Petrol)	C08-A (Diesel)	C08-AG (Petrol)	C08-A (Diesel)	C08-AG (Petrol)						
GEWICHT • POIDS • PESO	570 kg	541 kg	660 kg	637 kg	670 kg	643 kg	765 kg	740 kg	658 kg	632 kg	700 - 881 kg	1 100 kg	2 650 kg	2 865 kg	6 060 kg	6 390 kg
GESAMTBREITE • LARGEUR TOTALE • INGOMBRO TRASVERSALE	810 mm	810 mm	835 mm	835 mm	810 mm	810 mm	835 mm	835 mm	810 mm	810 mm	810/835 mm	950 mm	1 550 mm	1 550 mm	2 200 mm	2 200 mm
LADEKAPAZITÄT • CAPACITÉ DE CHARGE • CAPACITÀ DI CARICO	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	800 kg	1 150 kg	2 500 kg	2 500 kg	3 800 kg	3 500 kg
KAPAZITÄT KIPPMULDE • CAPACITÉ DE LA BENNE • CAPACITÀ DEL RIBALTABILE	0,36 m³	0,36 m³	0,34 m³	0,34 m³	0,36 m³	0,36 m³	0,34 m³	0,34 m³	0,42 m³	0,42 m³	0,34 - 0,42 m³	0,52 m³	1,24 m³	1,50 m³	2,3 m³	2,1 m³
HÖHE DER MULDENKANTE • HAUTEUR DU BORD DE L'AUGE • ALTEZZA DEL BORDO DELLA CANALETTA	739 mm	739 mm	739 mm	739 mm	1 350 mm	1 350 mm	1 350 mm	1 350 mm	790 mm	790 mm	739-1350 mm	325 mm	455 mm	730 mm	660 mm	890 mm
NETTOLEISTUNG • PUISSANCE NETTE • POTENZA NETTA	6,8 kW 9,2 PS	9,9 kW 13,5 PS	6,8 kW 9,2 PS	9,9 kW 13,5 PS	6,8 kW 9,2 PS	9,9 kW 13,5 PS	6,8 kW 9,2 PS	9,9 kW 13,5 PS	6,8 kW 9,2 PS	9,9 kW 13,5 PS	 10,3 kW 14,0 PS	7,5 kW / 2 800 U/min 10,2 PS	32,5 kW / 2 800 U/min 44,2 PS	32,5 kW / 2 800 U/min 44,2 PS	84 kW / 2 500 U/min 114,2 PS	84 kW / 2 500 U/min 114,2 PS



